

SD SERIES-SPECIFICATION DATA SHEET 1.15



Kirk Key Interlock Company

9048 Meridian Circle NW, North Canton, OH 44720

Phone: 234.209.9301 • Fax: 330.497.4400 • Toll Free: 800.438.2442

Website: www.kirkkey.com Email: sales@kirkkey.com

Camlock



The Camlock is a compact, threaded cylinder interlock designed to fit smaller-sized switchgear. The key is trapped or released according to the position of the cam. It is designed to be installed with provisions or bracketry provided by the breaker manufacturer. The Camlock can be linked to other camlocks with the proper bracketry.

The Camlock is manufactured so that it normally turns clockwise to trap the key. If counterclockwise rotation is required, a small set screw can be easily moved from one side of the interlock to the other to facilitate CCW rotation.

The Camlock is made from brass. The hex mounting nuts are zinc plated steel.

OPTIONS

- Stamp Key Interchange – specify one character code (A, B, 1, 2, etc.) to be stamped on the cylinder face and on the key. See SD Series Data Sheet 3.4 and 4.1 for details. Note: due to the small size of this interlock, two characters cannot be used for the key interchange.

HOW TO ORDER:

The item master number for the Camlock is KCAM00010. If a key interchange is to be stamped on the cylinder face and key, the item master number is KCAM00010S.

When ordering a Camlock for GE EntelliGuard G® Cassette Mounted Circuit Breakers please refer to GE installation instructions DEH-41500. Those instructions will direct you to order Kirk Camlock KCAMXXX10S or KCAMXXX11S depending upon the application. (Remove the "S" from the part number if the key interchange is not to be stamped)

SD SERIES-SPECIFICATION DATA SHEET 1.15



Kirk Key Interlock Company

9048 Meridian Circle NW, North Canton, OH 44720

Phone: 234.209.9301 • Fax: 330.497.4400 • Toll Free: 800.438.2442

Website: www.kirkkey.com Email: sales@kirkkey.com

Camlock

