

SD SERIES - SPECIFICATION DATA SHEET 3.2



www.kirkkey.com

Kirk Key Interlock Company

211 Wetmore Ave. S.E., Massillon, OH 44646

Phone: 330.833.8223 • Fax: 330.833.1528 • Toll Free: 800.438.2442

Email: sales@kirkkey.com

Mounting Bolts Hex Head



Hex Head Mounting Bolts

Stainless steel (18-8), hex head mounting bolts are available. Hex head mounting bolts will be supplied when the letter "M" is shown in the appropriate column of the interlock part number. Reference the SD Series Ordering Guide.

Standard mounting bolt sizes:

- a.) 3/8"-16 x 3/4" (for Type B & Unhoused Type SKRU)
- b.) 3/8"-16 x 1-3/4" (for Type F, T, D and DM)
- c.) 3/8"-16 x 2-1/4" (for Type D latchblock & Type U lock)
- d.) 1/4"-20 x 5/8" (for Type FN, TPS and SKPM)
- e.) 1/4"-20 x 1-3/4" (for Type NT)

Options:

The 3/8"-16 hex head bolts can be provided with a through hole in which a sealing wire can be secured.

SD SERIES - SPECIFICATION DATA SHEET 3.2



www.kirkkey.com

Kirk Key Interlock Company

211 Wetmore Ave. S.E., Massillon, OH 44646

Phone: 330.833.8223 • Fax: 330.833.1528 • Toll Free: 800.438.2442

Email: sales@kirkkey.com

Mounting Bolts Tamperproof



Tamperproof Mounting Bolts

Stainless steel (18-8) tamperproof mounting bolts are available. Button Head Socket bolts will be supplied when the letter "T" is shown in the appropriate column of the interlock part number. Reference the SD Series Ordering Guide.

Standard mounting bolt sizes:

- a.) 3/8"-16 x 3/4" (for Type B & Unhoused Type SKRU)
- b.) 3/8"-16 x 1-3/4" (for Type F, T, D and DM)
- c.) 3/8"-16 x 2-1/4" (for Type D latch block & Type U lock)
- d.) 1/4"-20 x 3/4" (for Type FN, TPS, and SKPM)
- e.) 1/4"-20 x 2" (for Type NT)

SD SERIES - SPECIFICATION DATA SHEET 3.2



www.kirkkey.com

Kirk Key Interlock Company

211 Wetmore Ave. S.E., Massillon, OH 44646

Phone: 330.833.8223 • Fax: 330.833.1528 • Toll Free: 800.438.2442

Email: sales@kirkkey.com

Mounting Bolts Tamperproof Tools



A tamperproof key tool or tamperproof bit tool is required to install the tamperproof mounting bolts.

- 3/8" Bolt Key (Part #21HKHKA) - shown at top of picture.
- 1/4" Bolt Key (Part #15HKHKA) - shown middle of picture.
- 3/8" Bolt Bit (Part #21HKHB) - shown at bottom of picture.