



| Numéro de catalogue. Catalog number. | Conducteur Conductor | Couleur Colour | C | L | T | Outils, ensemble de matrice et nombres de sertissages Tools, die set and number of crimps |
|-----------------------------------------|-------------------------|-------------------|------|------|------|----------------------------------------------------------------------------------------------|
| | | | | | | Y35, Y39, Y46* |
| YA1C-2N | 1 AWG | Green | 0.81 | 4.82 | 0.12 | U1CRT-1 (2) / U4CABT (2) |
| YA2C-2N | 2 AWG | Gray | 0.81 | 4.45 | 0.12 | U4CRT (2) / U6CABT (2) |
| YA25-2N | 1/0 AWG | Pink | 0.81 | 4.81 | 0.11 | U25RT (2) / U2CABT (2) |
| YA26-2N | 2/0 Str. | Black | 0.83 | 4.97 | 0.12 | U26RT (2) |
| YA27-2N | 3/0 Str. | Orange | 0.91 | 5.01 | 0.13 | U27RT (2) |
| YA28-2N | 4/0 Str. | Purple | 1.02 | 5.17 | 0.14 | U28RT (2) |
| YA29-2N | 250 kcmil | Yellow | 1.11 | 5.21 | 0.16 | U29RT (2) |
| YA30-2N | 300 kcmil | White | 1.20 | 5.64 | 0.16 | U30RT (4) / U28ART (4) |
| YA31-2N | 350 kcmil | Red | 1.29 | 5.68 | 0.18 | U31RT (4) / U29ART (4) |
| YA32-2N | 400 kcmil | Blue | 1.38 | 5.85 | 0.19 | U32RT (4) / U30ART (4) |
| YA34-2N | 500 kcmil | Brown | 1.52 | 6.06 | 0.23 | U34RT (4) / U31ART (4) |
| YA36-2N | 600 kcmil | Green | 1.69 | 6.59 | 0.27 | U36RT (4) / U32ART (4) |
| YA39-2N | 750 kcmil | Black | 1.89 | 6.87 | 0.27 | U39RT (4) / U36ART (4) |
| YA44-2N | 1000 kcmil | White | 2.17 | 7.14 | 0.33 | P44RT (4) |

Matériel: Cuivre étamé

Material: Tin plated copper

CONNECTEUR COMPRESSIBLE / COMPRESSIBLE CONNECTOR