



| Numéro de catalogue. Catalog number. | Hauteur (po). Height (in.) | Diamètre du filet X profondeur (po.) Thread diameter X depth (in.) | Voltage (V) | Poids (lbs/ch) Weight (lbs/ea) |
|---|-------------------------------|---|-------------|-----------------------------------|
| 2165 -1A | 1 | 1/4 (20) X 5/16 | 600 | 0.1 |
| 2165- 1B | 1-1/4 | 1/4 (20) X 5/16 | 600 | 0.1 |
| 1603- 1B | 1-3/8 | 3/8 (16) X 3/8 | 600 | 0.2 |
| 1603- 2A | 1-3/8 | 3/8 (16) X 3/8 | 600 | 0.2 |
| 2015- 1A | 1-1/2 | 1/4 (20) X 1/2 | 1 500 | 0.2 |
| 2015- 2A | 1-1/2 | 5/16 (18) X 7/16 | 1 500 | 0.2 |
| 2015- 3A | 1-1/2 | 3/8 (16) X 3/8 | 1 500 | 0.2 |
| 2015- 2B | 1-3/4 | 5/16 (18) X 7/16 | 2 000 | 0.25 |
| 2015- 3B | 1-3/4 | 3/8 (16) X 3/8 | 2 000 | 0.25 |
| 2015- 2C | 2 | 5/16 (18) X 7/16 | 2 300 | 0.3 |
| 2015- 3C | 2 | 3/8 (16) X 9/16 | 2 300 | 0.31 |
| 2015- 4C | 2 | 1/2 (13) X 5/8 | 2 300 | 0.3 |
| 2015- 3D | 2-1/4 | 3/8 (16) X 9/16 | 2 700 | 0.4 |
| 2015- 4D | 2-1/4 | 1/2 (13) X 5/8 | 2 700 | 0.4 |
| 1461- 1A | 2-1/8 | 3/8 (16) X 9/16 | 2 500 | 0.6 |
| 1461- 1B | 2-1/8 | 1/2 (13) X 5/8 | 2 500 | 0.6 |
| 1461- 1C | 2-1/8 | 5/8 (11) X 5/8 | 2 500 | 0.6 |

Matériel: Fibre de verre renforcé **Material:** Reinforced fiberglass

ISOLATEUR EN FIBRE DE VERRE / FIBERGLASS INSULATOR