



**PINCE / CLAMP TYPE #4**

PTS CAT. #: **C6001734**



**PINCE À BEC DE CANARD /  
 DUCKBILL CLAMP**

**CAPACITÉ ÉLECTRIQUE / ELECTRICAL RATING**

Capacité / Current Rating	[kA]	35
Courant Continu / Continuous Rating	[Amps]	400
Court-Circuit / Fault Current	<b>15 Cycles</b>	43 000
Court-Circuit / Fault Current	<b>30 Cycles</b>	30 000

MALT / GROUING

**CAPACITÉ MÉCANIQUE / MECHANICAL RATING**

Couple de Serrage / Recommended Torque	[Pouce/Lbs]/[Inch/Lbs]	250
Conducteur Maximal / Maximum Conductor	[Pouce]/[Inch]	566 kcmil Cu. – 900 kcmil ACSR (1.162")
Conducteur Minimum / Minimum Conductor	[Pouce]/[Inch]	# 6 sol. Cu. (0.162")
Câble de MALT Maximal / Maximum Jumper Range		4/0 avec manchon fileté 5/8"-11 UN/ With 5/8"-11 UNC threaded Lug
Câble de MALT Minimum / Minimum Jumper Range		# 2 avec manchon fileté 5/8"-11 UN/ With 5/8"-11 UNC threaded Lug
Poids / weight		1.5 Lbs / 0.7Kg.
Désignation ASTM / Designation ASTM	<b>F 855</b>	Type 1 – Classe A – Grade 5