




PINCE / CLAMP TYPE #8

PTS CAT. #: **C6002231**

PINCE À TÊTE PLATE /
FLAT FACE CLAMP



CAPACITÉ ÉLECTRIQUE / ELECTRICAL RATING

Capacité / Current Rating	[kA]	35
Courant Continu / Continuous Rating	[Amps]	400
Court-Circuit / Fault Current	15 Cycles	43 000
Court-Circuit / Fault Current	30 Cycles	30 000

CAPACITÉ MÉCANIQUE / MECHANICAL RATING

Couple de Serrage / Recommended Torque	[Pouce/Lbs]/[Inch/Lbs]	250
Conducteur Maximal / Maximum Conductor	[Pouce]/[Inch]	1 ½ " Angles 1 ½ " Barre Plate/Flat Bar
Conducteur Minimum / Minimum Conductor	[Pouce]/[Inch]	1/8 "
Câble de MALT Maximal / Maximum Jumper Range		4/0 avec manchon fileté 5/8"-11 UN/ With 5/8"-11 UNC threaded Lug
Câble de MALT Minimum / Minimum Jumper Range		# 2 avec manchon fileté 5/8"-11 UN/ With 5/8"-11 UNC threaded lug
Poids / weight		2 Lbs / 0.9 Kg
Désignation ASTM / Designation ASTM	F 855	Type III – Classe B – Grade 5

MALT / GROUING