



**PINCE / CLAMP TYPE M**

MANCHON LISSE / PLAIN LUG (ML)



MANCHON FILETÉ / THREADED LUG



(EXEMPLE : MF-MF-

**CAPACITÉ ÉLECTRIQUE / ELECTRICAL RATING**

Grandeur / Size (AWG)	# 2	1/0	2/0	4/0
Capacité / Current Rating [kA]	12	20	22	35
Courant Continu / Continuous Rating [Amps]	200	250	300	400
Court-Circuit / Fault Current <b>15 Cycles</b>	14 000	21 000	27 000	43 000
Court-Circuit / Fault Current <b>30 Cycles</b>	10 000	15 000	20 000	30 000

**CAPACITÉ MÉCANIQUE / MECHANICAL RATING**

Grandeur / Size (AWG)	# 2	1/0	2/0	4/0
Manchon Lisse / Plain Lug	X	X	X	X
Manchon Fileté / Threaded Lug	X	X	X	X
Poids / Weight [Lbs]/[Kg]	0.1 Lbs / 0.05 Kg	0.1 Lbs / 0.05 Kg	0.2 Lbs / 0.07 Kg	0.2 Lbs / 0.07 Kg
Désignation ASTM / Designation ASTM	<b>F 855</b>			

MALT / GROUING