



SD57N = sans / none

SD57S = avec lodgement a rotule /with socket clevis

Numéro de catalogue. Catalog number.	Gamme de serrage Clamping Range		Dimension po. / in.					Boulons en U U-Bolts		Force Ultime (lbs)	Poids (lbs)
	po. in.	ACSR (MCM)	A	B	C	D	R	#	Grosseur / Size	Ultimate Strength (lbs)	Weight (lbs)
<b>SD57N</b> <b>SD57S</b>	0.20 - 0.64	4-6/7 - 266.8-267	9.16	5 1/8	3/4	5/8	60 deg	3	1/2	15,000	3.2
<b>SD70N</b> <b>SD70S</b>	0.30 - 0.75	2 - 397.5 (18/1)	10 1/4	6 1/2	15/16	5/8	60 deg	4	1/2	20,000	4.7
<b>SD86N</b> <b>SD86S</b>	0.46 - 0.94	3/0-6/1 - 556-267	11-1/4	7 3/8	1 1/16	5/8	60 deg	4	1/2	25,000	5.4
<b>SD112N</b> <b>SD112S</b>	0.5 - 1.20	3/0-6/1 - 954-547	13 1/8	8 1/4	1 3/8	3/4	60 deg	5	1/2	30,000	8.4
<b>SD130N</b> <b>SD130S</b>	0.70 - 1.39	336.4 (26/7) - 1272 (54/19)	14	9 1/2	1 7/16	3/4	60 deg	5	5/8	30,000	13.2

**Note:** Autres dimensions disponible  
Other sizes available

Couple de serrage recommandé:  
1/2'' (480 lbs-po), 5/8'' (720 lb-po)  
Recommended torque 1/2'' (480 in-  
lbs), 5/8'' (720 in-lbs)

**Matériel:** Corps: Aluminium, Boulons Acier Galvanisé

**Material:** Body: Aluminum, Bolts Galvanized steel

## PINCE D'AMARRAGE À DÉRIVATION TRIANGLE DEADEND CLAMP