



Droit / Straight



Évasé / Flaired



Quincaillerie / Hardware

Numéro de catalogue. Catalog number.	Longueur total (po) Total length (in)	Ouverture (po.) Opening (in.)	Poids (lbs) Weight (lbs)
9876	96	3/4	5.3
<b>9878</b>	96	1-1/4	7.6
<b>9882</b>	96	2-1/4	14.7
<b>9884</b>	96	3-1/4	20
<b>9886</b>	96	3-3/4	21.6
<b>9888</b>	96	4-1/4	28
9889	96	5	33

Numéro de catalogue. Catalog number.	Longueur total (po) Total length (in)	Ouverture (po.) Opening (in.)	Poids (lbs) Weight (lbs)
————	————	————	————
<b>9878F</b>	96	1-1/4	8.4
<b>9882F</b>	96	2-1/4	16
<b>9884F</b>	96	3-1/4	22
<b>9886F</b>	96	3-3/4	23.75
<b>9888F</b>	96	4-1/4	31
9889F	96	5	36.5

Courroie ( 3 par long de 96'' )  
Strap ( 3 per 96'' length )



Numéro de catalogue. Catalog number.	Dimension du protège (po). Guard dimension (in.)	Diamètre des trous (po) Diameter of holes (in)	Poids (lbs) Weight (lbs)
<b>9890</b>	3/4	1/4	0.12
<b>9891</b>	1-1/4	1/4	0.15
<b>9892</b>	2-1/4	1/4	0.24
<b>9893</b>	3-1/4	5/16	0.60
<b>9894</b>	3-3/4	5/16	0.70
<b>9894-1/4</b>	4-1/4	5/16	0.75
<b>9895</b>	5	5/16	0.90

**Matériel:** Acier Galvanisé a chaud

**Material:** Hot dip galvanized steel

## PROTÈGE CABLE / U-CABLE GUARD