



Numéro de catalogue Catalog number	Diamètre et course de serrage (po.) Thread Diameter & Take Up (in.)	*Limite de la charge de travail (lbs) *Working load limit (lbs)	Poids (lbs) Weight (lbs)	Dimensions po. in.								
				A	J	K	M	N	R	S	X	BB
TB306EE	3/8 x 6	*1200	0.76	0.38	17.47	11.47	18.16	12.16	1.12	0.53	2.52	6.00
TB406EE	1/2 x 6	*2200	1.54	0.50	20.08	13.08	20.96	13.96	1.42	0.72	3.23	6.00
TB412EE	1/2 x 12	*2200	2.14	0.50	32.08	19.08	32.96	19.96	1.42	0.72	3.23	12.00
<b>TB506EE</b>	5/8 x 6	*3500	3.28	0.63	21.93	14.68	22.93	15.68	1.80	0.88	3.90	6.00
<b>TB512EE</b>	5/8 x 12	*3500	3.42	0.63	33.93	20.68	34.93	21.68	1.80	0.88	3.90	12.00
TB606EE	3/4 x 6	*5200	3.79	0.75	23.88	16.38	25.12	17.62	2.09	1.00	4.69	6.00
<b>TB612EE</b>	3/4 x 12	*5200	5.48	0.75	35.88	22.38	37.12	23.62	2.09	1.00	4.69	12.00
<b>TB618EE</b>	3/4 x 18	*5200	7.19	0.75	47.88	28.38	49.12	29.62	2.09	1.00	4.69	18.00
TB812EE	1 x 12	*10000	11.5	1.00	39.97	25.97	41.97	27.72	3.00	1.44	6.36	12.00

**\*La charge sécuritaire est 2.5 fois la charge de travail.**  
**La charge Ultime est 5 fois la charge de travail.**

**\*Proof load is 2.5 times working load**  
**Ultimate load is 5 times working load**

**Matériel:** Acier Galvanisé  
**Material:** Galvanized steel

## TENDEUR À VIS, ŒIL-OEIL/ TURNBUCKLE, EYE-EYE