



Numéro de catalogue Catalog number	Diamètre et course de serrage (po.) Thread Diameter & Take Up (in.)	*Limite de la charge de travail (lbs) *Working load limit (lbs)	Poids (lbs) Weight (lbs)	Dimensions po. in.								
				A	B	E	G	J	K	M	N	BB
TB306JJ	3/8 x 6	*1200	0.81	.38	.54	2.12	.87	16.14	10.14	17.38	11.38	6.00
TB406JJ	1/2 x 6	*2200	1.56	.50	.55	2.75	1.06	18.50	11.50	20.00	13.00	6.00
TB412JJ	1/2 x 12	*2200	2.4	.50	.55	2.75	1.06	30.50	17.50	32.00	19.00	12.00
TB506JJ	5/8 x 6	*3500	2.72	.63	.82	3.50	1.31	20.05	12.80	22.13	14.88	6.00
<b>TB512JJ</b>	5/8 x 12	*3500	3.91	.63	.82	3.50	1.31	32.05	18.80	34.13	20.88	12.00
TB606JJ	3/4 x 6	*5200	4.11	.75	1.03	4.18	1.50	21.50	14.00	24.10	16.60	6.00
<b>TB612JJ</b>	3/4 x 12	*5200	6.43	.75	1.03	4.18	1.50	33.50	20.00	36.10	22.60	12.00
TB618JJ	3/4 x 18	*5200	8.07	.75	1.03	4.18	1.50	45.50	26.00	48.10	28.60	18.00
TB812JJ	1 x 12	*10000	12.52	1.00	1.31	5.53	2.06	36.72	22.72	40.06	26.06	12.00

**\*La charge sécuritaire est 2.5 fois la charge de travail.**  
**La charge Ultime est 5 fois la charge de travail.**

**\*Proof load is 2.5 times working load**  
**Ultimate load is 5 times working load**

**Matériel:** Acier Galvanisé  
**Material:** Galvanized steel

**TENDEUR À VIS, MACHOIRE-MACHOIRE / TURNBUCKLE, JAW-JAW**