

**NEW**

# Rectangular Current Transformers

Now available for your revenue metering and general production needs in ground leakage and ground fault applications

## Features and Benefits

- High accuracy and extended range capable
- Made of Meramec's proprietary high-grade material and epoxy encapsulated
- Domestically produced then fully tested, proven, and certified
- Built to specifications of Meramec's industry-leading 99.98% quality rating
- Rated for indoor service (0.72kV/10kV BIL)
- Custom-engineered units available



## RELV-CT General Technical Data

Application	Relaying
Inner Diameter	13.38" x 44.25" [340 x 1124 mm]
Perimeter Dimensions	19.50" [495 mm] x 50.38" [1280 mm]
Depth	3.50" [89 mm]
Primary Currents	From 50 amps
Secondary Current	5/1 amps
Rated Frequency	60/50Hz
Standards*	IEEE C57.13/CSA 60044-1/IEC 61869
Basic Insulation Level	0.6kV, 10kV BIL
Approximate Weight	160 lbs

\*Multiple accuracy classes available upon request

## Catalog Info

Catalog Number	Ratio	Accuracy		
		Metering	Relaying	
Single-Ratio		CSA/IEEE	CSA/IEC	IEEE
<b>RELV-500-1344</b>	50:5			50:5



Learn more about Meramec.  
Contact your Hubbell sales representative or visit  
[www.meramecusa.com](http://www.meramecusa.com)



A Hubbell brand