



PINCE / CLAMP TYPE M

MANCHON LISSE / PLAIN LUG (ML)



MANCHON FILETÉ / THREADED LUG



(EXEMPLE : MF-MF-2/0E3)

CAPACITÉ ÉLECTRIQUE / ELECTRICAL RATING

Grandeur / Size (AWG)	# 2	1/0	2/0	4/0
Capacité / Current Rating [kA]	14	21	27	43
Courant Continu / Continuous Rating [Amps]	200	250	300	400
Court-Circuit / Fault Current 15 Cycles	14 000	21 000	27 000	43 000
Court-Circuit / Fault Current 30 Cycles	10 000	15 000	20 000	30 000

CAPACITÉ MÉCANIQUE / MECHANICAL RATING

Grandeur / Size (AWG)	# 2	1/0	2/0	4/0
Manchon Lisse / Plain Lug	X	X	X	X
Manchon Fileté / Threaded Lug	X	X	X	X
Poids / Weight [Lbs]/[Kg]	0.1 Lbs / 0.05 Kg	0.1 Lbs / 0.05 Kg	0.2 Lbs / 0.07 Kg	0.2 Lbs / 0.07 Kg
Désignation ASTM / Designation ASTM	F 855			

MALT / GROUNDING